

“continuous duty” diaphragm seal, welded, with threaded connection



Diaphragm seals are designed to isolate the sensing element of pressure gauges, pressure switches and electronic pressure transmitter from process fluids which may be corrosive, viscous, sediment and/or with a high temperature. If the instrument is removed accidentally or in case of liquid filling leakage the diaphragm moves to the upper cup preventing damages and a possible process liquid leakage. Thanks to an exclusive calibration system the pressure gauge is able to withstand an overpressure of 210 bar without the support of a pressure control switch.

4.2B0 - MGS9/2B

Design: ASME B40.2

Working pressure: *from -30...0 INHG to 0...2320 psi* (from -1...0 to 0...160 bar).

“Continuous duty”: *3000 psi* (210 bar) as per ASME B40.2.

Process temperature: *-49...+302°F* (-45°C...+150°C.)

Accuracy (1): (add to instrument accuracy) $\pm 0,5\%$ for direct mounting, $\pm 1\%$ for capillary mounting.

Instrument connection: AISI 304 st.st.

Diaphragm material:

4 - AISI 316L st.st.,

6 - Monel 400,

9 - Hastelloy C 276,

B - Tantalum,

J - Alloy 600;

I - Alloy 825;

Gaskets: PTFE up to +482°F (+250°C).

Process connection:

5 - AISI 316L st.st.

6 - Monel 400

9 - Hastelloy C 276.

Clamp nuts and bolts: high resistance steel.

Filling liquids: Silicon oil.

Special overpressure: *3000 psi for 1 hour* (210 bar) (2) (3).



(1) at 68°F (20 °C) process temperature (or state temperature when ordering)

(2) on request only, pressure gauge/pressure switch assembling only

(3) Vacuum and compound gauges excluded

**"continuous duty" diaphragm seal
welded, with threaded connection**

MGS9/2B



F	D	ch	H	h	L	Weight
41M - G 1/2 B	3.15"	0.87"	3.54"	2.79"	0.79"	2.36 lbs
43M - 1/2 NPT	(80)	(22)	(90)	(35,5)	(20)	(1,070 kg)

dimensions : inches (mm)

F	D	ch	H	h	Weight
43F 1/2 NPT F	3.15"	1.06"	3.23"	1.08"	2.34 lbs
	(80)	(27)	(82)	(27,5)	(1,060 kg)

dimensions : inches (mm)

ASSEMBLING

All diaphragm seals are mounted on the instruments and fixed by an aluminium protection label. For applications with capillary: should diaphragm seal and instrument not be at the same level, instrument adjustment is required). (For use and installation, see data sheet "4")

D - Direct	9 - Capillary AISI304 st.st., AISI304 st.st. armoured, 36.37" max (6 mt max)
I - Nude capillary AISI304, 36.37" max (6 mt max)	6 - Capillary AISI316 st.st., AISI316 st.st. armoured, 36.37" max (6 mt max)

FILLING FLUIDS and process fluid temperature

Fluid	Vacuum	Pressure	Fluid	Vacuum	Pressure
Standard silicon oil	-40...+122°F (-40...+100°C)	-40...+302°F (-40...+150°C)	E - Fluorinated liquid "E"	-40...+212°F (-40...+100°C)	-40...+302°F (-40...+150°C)
B - Silicon oil "B"	-40...+302°F (-40...+150°C)	-40...+482°F (-40...+250°C)	F - Silicon oil "C"	-130...+176°F (-90...+80°C)	-130...+302°F (-90...+150°C)
C - Silicon oil "C"	-14...+392°F (-10...+200°C)	-14...+662°F (-10...+350°C)	G - Mineral food oil "G"	-14...+302°F (-10...+150°C)	-14...+392°F (-10...+200°C)
D - Silicon oil "D"	-14...+392°F (-10...+200°C)	-14...+752°F (-10...+400°C)			

OPTIONS

C05 - Helium Test (1)
E30 - Nace version MR0103/MR0175 (ISO 15156) (2)
TS5 - AISI316L stainless steel washing plug, 1/4" NPT
P04 - Dye penetrant test
BAI - Stainless steel fixing bolts (5)
S40 - Max overpressure 3000 psi (210 bar) (3) (4)
MPP - PTFE diaphragm protection, for temperature up to 302 °F (150 °C) (3)
Special process connections (1) : 1/4" NPTF; 3/4" NPTF; 3/4 NPTM

- (1) on models with AISI316L process connection only
- (2) Stainless steel process connection and Monel 400 or Hastelloy C276 diaphragm

- (3) Except for vacuum and compound gauges
- (4) for pressure gauge/pressure switch assembling only
- (5) max 100 bar

"HOW TO ORDER" SEQUENCE

Section/Model/Connection material/Diaphragm material/Process Connection/Instrument connection/Assembling/Options
4 2B0 5 4, 6, 9 41M 41F - G 1/2 F D B...G
6 B, J, I 43M 43F - 1/2NPT F 1, 9, 6 C05...MPP
9 43F

Copyright © Nuova Fima srl. All rights reserved. Any part of this publication should not be reproduced without a written Nuova Fima's srl approval



REG - 1102 IN ORDER TO IMPROVE THEIR PRODUCTION, MESSRS. NUOVA FIMA RESERVE THE RIGHT TO THEMSELVES TO MAKE ALL THE MODIFICATIONS THAT THEY DEEM INDISPENSABLE AT ANY TIME. UPDATED DATA SHEETS ARE AVAILABLE ON SITE: www.nuovafima.com