



HIGH PRESSURE BRASS FLOW SWITCH

Up to 1500 psi, Fixed Set point, Up to 2.0 GPM, Rugged Brass Body



The **Series P8 High Pressure Brass Flow Switch** is ideal for high in-line pressures. Set points range from 0.25 to 2.0 GPM for liquid flow.

BENEFITS/FEATURES

- Integrates a one-piece magnetic PPS composite piston to handle pressure up to 1500 psi
- Less susceptible to clogging than other high in-line pressure switches with 100 micron filtration

APPLICATIONS

- Industrial cleaning equipment
- High pressure lubrication systems

MODEL CHART

Model	Actuation Set Point GPM (LPM)
P8-11	0.25 (.95)
P8-12	0.50 (1.89)
P8-13	1.0 (3.79)
P8-14	1.5 (5.68)
P8-15	2.0 (7.57)

SPECIFICATIONS

Service: Compatible liquids.

Wetted Materials: Housing: Brass; Piston: PPS composite, epoxy; Spring: 316 SS; O-ring: Fluorocarbon.

Temperature Limits: -20 to 275°F (-28 to 135°C).

Pressure Limits: 1500 psi (103.4 bar).

Accuracy: ±20% of set point.

Switch Type: SPST, NO.

Electrical Rating: .17 A @ 120 VAC, .08 A @ 240 VAC, .13 A @ 120 VDC, .06 A @ 240 VDC.

Electrical Connection: No. 22 AWG, 24" (61 cm), polymeric leads.

Process Connections: 3/8" male NPT.

Mounting Orientation: Any position. Set points shown are based on vertical, inlet down position.

Required Filtration: 100 microns or better.

Weight: 6 oz (.17 kg).

Agency Approvals: CE.