

Pneumatic hand test pumps // -0.95...60 bar

P40.2 // P60



Highlights – P40.2

- Testing, adjustment and calibration of all types of pressure gauges
- 3 in 1: vacuum, low pressure and medium pressure calibration
- Exact adjustment in the mbar range thanks to ultra-fine thread pitch and large volume control valve
- Tool-free change between positive pressure and vacuum generation

Highlights – P60

- Like P40.2
- Single pneumatic hand pressure pump up to 60 bar

Technical Data

	P40.2	P60
Type		
Pressure ranges		
→ Negative pressure	-0.95 bar	-0.95 bar
→ Positive pressure	40 bar	60 bar
Pressure medium	Air	
Connections		
Reference pressure gauge	G $\frac{1}{4}$	
Test sample	G $\frac{1}{4}$ with quick coupling and pressure hose (1 m)	
Basic		
Dimensions	Approx. 240 x 170 x 50 mm	
Weight	Approx. 1.1 kg	
Solid		
Dimensions (case)	Approx. 450 x 370 x 110 mm	
Weight	Approx. 4.2 kg	
+ Adapter kit	Chrome-plated brass, G $\frac{1}{8}$, G $\frac{1}{4}$, G $\frac{3}{8}$, G $\frac{1}{2}$, $\frac{1}{8}$ NPT, $\frac{1}{4}$ NPT, $\frac{1}{2}$ NPT, M12 x 1.5, M20 x 1.5, G $\frac{1}{8}$, G $\frac{1}{4}$	
+ Seal kit	PA flat gaskets and O-rings	

Article numbers

Order code		
Type	Version	Order number
P40.2	Basic	EPPM040EBL0000
	Solid (incl. case and adapter)	EPPM0400BL0000
P60	Basic	EPPM060EBL0000
	Solid (incl. case and adapter)	EPPM0600BL0000