

Accessoires // Test pumps // Digital pressure gauges



Case



DAKKS-Certificate



Dirt trap



Adapter G 1/4 - G 1/2



Pressure hose

For pneumatic test pumps		Order code
Hose	Polyamid, 1 m, chromed cap nut G 1/4 (female)	EPPM040SCHLA01
DIN adapter set	Chromed brass, 11 adapter, G 1/4 (female) - xxx	EPPM040ADAPT01
DIN single adapter	Chromed brass, lasered, G 1/4 (male) -xxx	
	G 1/4 A - G 1/8 I	FHP011
	G 1/4 A - G 3/8 I	FHP012
	G 1/4 A - G 1/2 I	FHP013
	G 1/4 A - NPT 1/8 I	FHP014
	G 1/4 A - NPT 1/4 I	FHP015
	G 1/4 A - NPT 1/2 I	FHP016
	G 1/4 A - M12 x 1,5 I	FHP017
	G 1/4 A - M20 x 1,5 I	FHP018
	G 1/4 A - G 3/8 A	FHP019
	G 1/4 A - G 1/4 A	FHP020
	G 1/4 A - G 1/4 I	FHP021
DIN seal set for DIN adapter	Different o-rings and thread tape seals in plastic box	EPPM040DICHT01
reducing adapter P40 adapter set	Chromed brass, G 1/4 (male) - G 3/8 (female)	EPPM040ADAPP40
Dirt trap	Up to max. 35 bar	EME8IDT6001000
Service kit seal set P40.2/ P60	Internal main piston and valve seals	EPPM040DICHT02
Fine adjust/ release valve	Complete valve system	EPPM040REGVE01
Replacement valve P40.2/ P60	Inlet and outlet valve incl. seals for replacement	EPPM040VENTIL01
Case blue P4	SIKA logo, foam lining and rigid foam inlay	XHP 180
Case blue P40.2/ P60	SIKA logo, foam lining and rigid foam inlay	EPPM040KOFFE01
Case grey P40.2/ P60	Neutral version, foam lining and rigid foam inlay	EPPM040KOFFE02
Rotary union	Brass G 1/4 (male) - G 1/2 (female)	EPPM040WIRBEL01

Article numbers

For hydraulic test pumps		Order code
Hose (1 m)	Polyamide, MiniMess®, chromed cap nut MM1620 (female)	XHP104
Hose (2 m)	Polyamide, MiniMess®, chromed cap nut MM1620 (female)	XHP117
High pressure hose P1000.2	Chromed cap nut with 2 adapters G $\frac{1}{4}$ (male) - G $\frac{1}{4}$ (female)	EME8HP10000000
Pressure gauge connection	MiniMess®, bulk head, chromed steel, MM1620 (male) - G $\frac{1}{4}$ (female)	XHP103
Testpoint	MiniMess®, coupling, chromed steel MM1620 (male) - G $\frac{1}{4}$ (male)	XHP214
Rotary union	MiniMess® direct connection, chromed steel M1620 (female) - G $\frac{1}{4}$ (female)	EME81620I-G14I
DIN adapter set	Stainless steel, 11 adapter, G $\frac{1}{4}$ (male) - xxx	EPPM700ADAPT01
DIN single adapter	Stainless steel, lasered, G $\frac{1}{4}$ (male) - xxx	
	G $\frac{1}{4}$ A - G $\frac{1}{8}$ I	FHP033
	G $\frac{1}{4}$ A - G $\frac{3}{8}$ I	FHP034
	G $\frac{1}{4}$ A - G $\frac{1}{2}$ I	FHP035
	G $\frac{1}{4}$ A - NPT $\frac{1}{8}$ I	FHP022
	G $\frac{1}{4}$ A - NPT $\frac{1}{4}$ I	FHP036
	G $\frac{1}{4}$ A - NPT $\frac{1}{2}$ I	FHP023
	G $\frac{1}{4}$ A - NPT $\frac{3}{8}$ I	FHP024
	G $\frac{1}{4}$ A - M12 x 1,5 I	FHP037
	G $\frac{1}{4}$ A - M20 x 1,5 I	FHP038
	G $\frac{1}{4}$ A - G $\frac{1}{8}$ A	FHP039
	G $\frac{1}{4}$ A - G $\frac{1}{4}$ A	FHP040
	G $\frac{1}{4}$ A - G $\frac{1}{4}$ I	FHP041
DIN seal set for DIN adapter	Different o-rings and thread tape seals in plastic box	EPPM040DICHT01
Cone seal Ref. P, Q, R, J	>1500 bar	EME8AECONO000
Hydraulic oil	plastic bottle, 0.25 litre	EZHÖ0100000000
Case blue P700.3 / P1000.2	SIKA logo, foam lining and rigid foam inlay	XHP 212

For digital pressure gauges		Order code
All types	DAkKS certificate (10 measuring points, no vacuum)	EKDRUCK000000D
	SIKA works certificate (10 measuring points)	EKDRUCK000000W
Type P	RS 232 C cable	EME8AEQCCABLE0
	Linearisation type P (0.05%): accuracy 0.025 % full scale (from ≥ 10 bar)	On request
Type P / J	Software calibration (PresKal)	EME8AEPCSW0000
	Software monitoring (DEMO)	EME8AESWTDEMKA
Type J	Software Datalogger (Analyzer Light)	EME8AESWANALLI
Type L-Ex / E-Ex / D-Ex	Oil and greasefree version up to max. 200 bar, 60 °C	On request